

## Docking Station for Multi-Gas Detectors



The POLI MonoDock (MP400T) is a docking and calibration station for the POLI Multi-Gas Detectors. The MP400T provides fast and easy calibration or bump testing: just place the POLI in the bay, connect the cable, and push start. All calibrations and bump test results are stored in on-board memory as a compliance record downloadable separate from the instruments themselves. The docking station is designed to operate with the four commonly measured gases oxygen (O<sub>2</sub>), carbon monoxide (CO), hydrogen sulfide (H<sub>2</sub>S), methane (CH<sub>4</sub>), plus isobutylene for PID bump/calibration. The MonoDock has rechargeable batteries and is portable for remote use.

### Features, Functions and Benefits

- **Simple & Fast:** One-button operation for either bump test or calibration
- **High Capacity:** 2,000 calibration or bump record storage in reliable FLASH Memory
- **Convenient:** Records can be downloaded without the POLI in place
- **Portable:** Battery power for up to 1000 bump tests
- **Robust:** All-in-one hard case



**POLI MonoDock**

# POLI MonoDock Specifications

## POLI MonoDock MP400T Specifications

<b>Size</b>	9.2 x 7.5 x 4.3 in (23.5 x 19.0 x 10.7 cm)
<b>Weight</b>	4.4 lbs. (2.0 kg)
<b>Number of Units</b>	One (1) POLI Pump Monitor
<b>Battery</b>	Rechargeable Lithium battery, up to 1000 bump tests on a single charge
<b>Temperature</b>	32°F to 122°F (0°C to 50°C)
<b>Humidity</b>	5 to 95% relative humidity (non-condensing)
<b>Event Log</b>	2000 Calibration or Bump records
<b>Power &amp; Communications Connection</b>	USB (Type A)
<b>Test Gas Supply</b>	<ul style="list-style-type: none"><li>• Cylinder(s) &amp; regulator(s) (not included) outside MonoDock</li><li>• Demand flow regulator(s) required</li><li>• Built-in pump for air or test gas</li></ul>
<b>Gas Connections</b>	<ul style="list-style-type: none"><li>• Quick-connects for 6-mm o.d. tubing:</li><li>• 2 Test gas inlets for calibration/bump</li><li>• Air inlet for zeroing</li></ul>
<b>Calibration Gases*</b>	<ul style="list-style-type: none"><li>• Gas mix with up to 4 gases:<ul style="list-style-type: none"><li>• Oxygen</li><li>• Carbon Monoxide</li><li>• Hydrogen Sulfide</li><li>• Methane</li></ul></li><li>• Isobutylene (for PID)</li></ul>
<b>Safety Certifications</b>	For use in non-hazardous locations
<b>Warranty</b>	1 year

\* Operation with other toxic gases is not available at this time. Check with mPower for availability.

**Distributed By:**



*\* Due to ongoing research and product improvement, specifications are subject to change without notice \**